

Package ‘pedMermaid’

May 9, 2026

Title Pedigree Mermaid Syntax

Version 1.0.2

Description Generate Mermaid syntax for a pedigree flowchart from a pedigree data frame. Mermaid syntax is commonly used to generate plots, charts, diagrams, and flowcharts. It is a textual syntax for creating reproducible illustrations. This package generates Mermaid syntax from a pedigree data frame to visualize a pedigree flowchart. The Mermaid syntax can be embedded in a Markdown or R Markdown file, or viewed on Mermaid editors and renderers. Links' shape, style, and orientation can be customized via function arguments, and nodes' shapes and styles can be customized via optional columns in the pedigree data frame.

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.1

Imports grDevices, stats

Suggests DiagrammeR, knitr, rmarkdown

VignetteBuilder knitr

URL <https://github.com/nilforooshan/pedMermaid>

BugReports <https://github.com/nilforooshan/pedMermaid/issues>

NeedsCompilation no

Author Mohammad Ali Nilforooshan [aut, cre] (ORCID:
<<https://orcid.org/0000-0003-0339-5442>>)

Maintainer Mohammad Ali Nilforooshan <m.a.nilforooshan@gmail.com>

Repository CRAN

Date/Publication 2024-04-09 16:40:02 UTC

Contents

mermaid_md	2
mermaid_rmd	4
Index	7

mermaid_md

*Generate Mermaid syntax for a pedigree flowchart in Markdown***Description**

Generate Mermaid syntax for a pedigree flowchart in Markdown

Usage

```
mermaid_md(
  ped,
  orient = "TB",
  type = "arrow",
  curve = "basis",
  dash = "N",
  lwd = 2,
  color = "black"
)
```

Arguments

ped : A data frame with the mandatory columns ID, SIRE, and DAM, and the optional columns TextColor, BgColor, BorderColor, RoundBorder, DashBorder, and lwd. The optional columns define (child) node-specific shape and style (corresponding to the ID column). The order of columns does not matter, but column names do matter and case-sensitive.

ped columns:

ID : Numeric or alphanumeric individual identifications.

SIRE : Sire identifications. Missing sires are denoted as 0.

DAM : Dam identifications. Missing dams are denoted as 0.

TextColor : Child (corresponding to ID) node's text color (valid color names and valid hex color codes). If this column is missing, the default color ("black" or "#000000") is used. Also, NA enforces the default color.

BgColor : Child (corresponding to ID) node's background color (valid color names and valid hex color codes). If this column is missing, the default color ("#ECECFE") is used. Also, NA enforces the default color.

BorderColor : Child (corresponding to ID) node's border color (valid color names and valid hex color codes). If this column is missing, the default color

("#9370DB") is used. Also, NA enforces the default color.

RoundBorder : Child (corresponding to ID) node's border shape (90° vs rounded edges). This column receives "Y" (rounded edges), "N" (90° edges), and NA (equivalent to the default value). If this column is missing, the default border shape ("N") is used.

DashBorder : Child (corresponding to ID) node's border line style (dashed vs solid). This column receives "Y" (solid line), "N" (dashed line), and NA (equivalent to the default value). If this column is missing, the default border line style ("N") is used.

lwd : Child (corresponding to ID) node's border line width. This column receives values > 0 , ≤ 5 , and NA (equivalent to the default value). If this column is missing, the default value (1) is used.

orient	: Defines the orientation of the flowchart ("TB" for top-to-bottom vs "LR" for left-to-right). If no input is provided, the default orientation ("TB") is used.
type	: Defines the type of links in the flowchart ("arrow" vs "line"). If no input is provided, the default link type ("arrow") is used.
curve	: Defines the shape of links in the flowchart ("basis", "bumpX", "bumpY", "cardinal", "catmullRom", "linear", "monotoneX", "monotoneY", "natural", "step", "stepAfter", and "stepBefore"). If no input is provided, the default link shape ("basis") is used.
dash	: Defines the style of links in the flowchart ("N" for solid line vs "Y" for dashed line). If no input is provided, the default link style ("N") is used.
lwd	: Defines the width of links in the flowchart (> 0 and ≤ 5). If no input is provided, the default value (2) is used.
color	: Defines the color of links in the flowchart (a valid color name or a valid hex color code). If no input is provided, the default color ("black" or "#000000") is used.

Value

: A vector of character strings. Each character string is a Mermaid syntax line. Assuming the returned output is saved in object `x`, use `cat(x, sep = "\n")` to display the output on-screen, and `cat(x, sep = "\n", file = "output.txt")` or `write(x, file = "output.txt")` to write the output into a file.

Examples

```
# A sample pedigree data frame with only the three mandatory columns.
ped <- data.frame(ID = 1:7, SIRE = c(0, 0, 1, 0, 3, 0, 5), DAM = c(0, 0, 2, 2, 4, 0, 6))

# Example 1: A pedigree Mermaid syntax without customizations.
x <- mermaid_md(ped)
# Read the "Value" part about displaying the output on-screen and writing it into a file.
```

```

# Example 2: Repeat example 1. Change arrow links to lines and the orientation to horizontal.
x <- mermaid_md(ped, orient = "LR", type = "line")

# Example 3: Repeat example 1. Pink background and round border edges for females (2, 4, 6).
ped$BgColor <- c(NA, "pink", NA, "pink", NA, "pink", NA)
ped$RoundBorder <- c(NA, "Y", NA, "Y", NA, "Y", NA)
x <- mermaid_md(ped)

# Example 4: Repeat example 3. Ticker border line for individuals in the control group (2, 5, 7).
ped$lwd <- c(1, 3, 1, 1, 3, 1, 3)
x <- mermaid_md(ped)

# Example 5: Use the default value and NA alternatively. This is not different from example 4.
ped$lwd <- c(NA, 3, NA, NA, 3, NA, 3)
x <- mermaid_md(ped)

# Example 6: Repeat example 1. Change link curve to "step" and green dashed.
x <- mermaid_md(ped[, c("ID", "SIRE", "DAM")],
  curve = "step", color = "#00FF00", dash = "Y")

```

mermaid_rmd

Generate Mermaid syntax for a pedigree flowchart in Markdown & R Markdown

Description

Generate Mermaid syntax for a pedigree flowchart in Markdown & R Markdown

Usage

```
mermaid_rmd(ped, orient = "TB", type = "arrow")
```

Arguments

ped : A data frame with the mandatory columns ID, SIRE, and DAM, and the optional columns BgColor, BorderColor, RoundBorder, DashBorder, and lwd. The optional columns define (child) node-specific shape and style (corresponding to the ID column). The order of columns does not matter, but column names do matter and case-sensitive.

ped columns:

ID : Numeric or alphanumeric individual identifications.

SIRE : Sire identifications. Missing sires are denoted as 0.

DAM : Dam identifications. Missing dams are denoted as 0.

BgColor : Child (corresponding to ID) node's background color (valid color names and valid hex color codes). If this column is missing, the default color ("ECECFE") is used. Also, NA enforces the default color.

BorderColor : Child (corresponding to ID) node's border color (valid color names and valid hex color codes). If this column is missing, the default color ("9370DB") is used. Also, NA enforces the default color.

RoundBorder : Child (corresponding to ID) node's border shape (90° vs rounded edges). This column receives "Y" (rounded edges), "N" (90° edges), and NA (equivalent to the default value). If this column is missing, the default border shape ("N") is used.

DashBorder : Child (corresponding to ID) node's border line style (dashed vs solid). This column receives "Y" (solid line), "N" (dashed line), and NA (equivalent to the default value). If this column is missing, the default border line style ("N") is used.

lwd : Child (corresponding to ID) node's border line width. This column receives values > 0 , ≤ 5 , and NA (equivalent to the default value). If this column is missing, the default value (1) is used.

orient : Defines the orientation of the flowchart ("TB" for top-to-bottom vs "LR" for left-to-right). If no input is provided, the default orientation ("TB") is used.

type : Defines the type of links in the flowchart ("arrow" vs "line"). If no input is provided, the default link type ("arrow") is used.

Details

The Mermaid syntax generated by the `mermaid_md` function can be embedded in Markdown files and Markdown renders such as GitHub, but not in R Markdown. Currently, Mermaid flowcharts in R Markdown have more limitations in terms of shape and style customizations, and the required syntax is less compact. Note that the generated syntax by this function can be embedded in both R Markdown and Markdown.

Value

: A vector of character strings. Each character string is a Mermaid syntax line. Assuming the returned output is saved in object `x`, use `cat(x, sep = "\n")` to display the output on-screen, and `cat(x, sep = "\n", file = "output.txt")` or `write(x, file = "output.txt")` to write the output into a file.

Examples

```
# A sample pedigree data frame with only the three mandatory columns.
ped <- data.frame(ID = 1:7, SIRE = c(0, 0, 1, 0, 3, 0, 5), DAM = c(0, 0, 2, 2, 4, 0, 6))
```

```
# Example 1: A pedigree Mermaid syntax without customizations.
x <- mermaid_rmd(ped)
# Read the "Value" part about displaying the output on-screen and writing it into a file.

# Example 2: Repeat example 1. Change arrow links to lines and the orientation to horizontal.
x <- mermaid_rmd(ped, orient = "LR", type = "line")

# Example 3: Repeat example 1. Pink background and round border edges for females (2, 4, 6).
ped$BgColor <- c(NA, "pink", NA, "pink", NA, "pink", NA)
ped$RoundBorder <- c(NA, "Y", NA, "Y", NA, "Y", NA)
x <- mermaid_rmd(ped)

# Example 4: Repeat example 3. Ticker border line for individuals in the control group (2, 5, 7).
ped$lwd <- c(1, 3, 1, 1, 3, 1, 3)
x <- mermaid_rmd(ped)

# Example 5: Use the default value and NA alternatively. This is not different from example 4.
ped$lwd <- c(NA, 3, NA, NA, 3, NA, 3)
x <- mermaid_rmd(ped)
```

Index

mermaid_md, 2, 5
mermaid_rmd, 4