

Package ‘vecvec’

June 4, 2026

Title Construct Mixed Type Data Structures with Vectors of Vectors

Version 1.1.0

Description Mixed type vectors are useful for combining semantically similar classes. Some examples of semantically related classes include time across different granularities (e.g. daily, monthly, annual) and probability distributions (e.g. Normal, Uniform, Poisson). These groups of vector types typically share common statistical operations which vary in results with the attributes of each vector. The 'vecvec' data structure facilitates efficient storage and computation across multiple vectors within the same object.

License MIT + file LICENSE

Imports rlang, S7, stats, vctrs

Suggests lifecycle, testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

URL <https://pkg.mitchelloharawild.com/vecvec/>,
<https://github.com/mitchelloharawild/vecvec>

BugReports <https://github.com/mitchelloharawild/vecvec/issues>

Config/roxygen2/version 7.3.3.9000

NeedsCompilation no

Author Mitchell O'Hara-Wild [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-6729-7695>>)

Maintainer Mitchell O'Hara-Wild <mail@mitchelloharawild.com>

Repository CRAN

Date/Publication 2026-06-04 05:10:03 UTC

Contents

class_vecvec	2
is_vecvec	3
masked-cor	3

unvecvec	4
vecvec	5
vecvec_apply	6
vecvec_apply_fn	6
vecvec_register	7

Index 9

class_vecvec	<i>S7 class for vecvec</i>
--------------	----------------------------

Description

class_vecvec() constructs a new vecvec object from a list of vectors. It is designed to be performant with minimal checks on the inputs. Direct use of class_vecvec() is useful for developers, but for users it is recommended to use [vecvec\(\)](#) to create vecvec objects.

Usage

```
class_vecvec(x = list(), i = seq_len(sum(lengths(x))))
```

Arguments

x	An unnamed list of arbitrary vectors. The vectors can be of different types and lengths, but they must all be vectors (according to vctrs::vec_is). Adjacent vectors of the same type will be combined together into a single vector.
i	A vector of integers specifying the location of each element in x as if they were combined in order. The values in i must be between 1 and the total number of elements across all vectors in x, and can contain duplicates. If not provided, it defaults to a sequence from 1 to the total number of elements across all vectors in x.

Value

A vector of vectors of S7 object of class class_vecvec.

Examples

```
# Create a vecvec prototype
class_vecvec()

# Construct a vecvec from a list of vectors
class_vecvec(list(letters, rnorm(10)))

# Fully specify a vecvec with locations
class_vecvec(
  x = list(letters, rnorm(10)),
  i = c(1:3, 27:31, 26:4, 32:36)
)
```

is_vecvec	<i>Test if an object is a vecvec</i>
-----------	--------------------------------------

Description

Test if an object is a vecvec

Usage

```
is_vecvec(x)
```

Arguments

x Object to test.

Value

TRUE if x inherits from class_vecvec, FALSE otherwise.

See Also

[vecvec\(\)](#) to create a vecvec object.

Examples

```
vv <- vecvec(1:3, letters)
is_vecvec(vv)
is_vecvec(1:3)
```

masked-cor	<i>Correlation, Variance and Covariance</i>
------------	---

Description

var, cov, and cor compute the variance of x and the covariance or correlation of x and y if these are vectors. If x and y are matrices then the covariances (or correlations) between the columns of x and the columns of y are computed.

These functions mask and wrap the [stats::var](#), [stats::cov](#), and [stats::cor](#) functions to add support for vecvec objects. More details can be found in the documentation for those functions.

Usage

```
var(x, ...)
```

```
cov(x, ...)
```

```
cor(x, ...)
```

Arguments

`x` a numeric vector, matrix or data frame.
`...` Additional arguments passed to `stats::var`, `stats::cov`, and `stats::cor`.

See Also

`stats::var()`, `stats::cov()`, `stats::cor()`

unvecvec

Coerce a vector of vectors to a single typed vector

Description**[Stable]**

Flattens a `vecvec` into a plain R vector by casting all elements to a common type. This is the inverse of `vecvec()`.

Type resolution follows `vctrs` coercion rules: when `ptype` is `NULL` the common type is determined automatically from the slots of `x` via `vctrs::vec_ptype_common()`. If no common type can be found (e.g. all slots are empty), the result falls back to `logical()`.

Usage

```
unvecvec(x, ptype = NULL)
```

Arguments

`x` A `vecvec` object.
`ptype` A prototype specifying the desired output type, e.g. `character()` or `numeric()`. If `NULL` (the default), the common type is inferred from the elements of `x` using `vctrs::vec_ptype_common()`, falling back to `logical()` when no common type can be determined. Passing an explicit `ptype` is useful when you need a guaranteed output type regardless of what `x` contains, or when automatic inference would pick an undesirable type.

Value

A vector of length `length(x)` and type `ptype` (or the inferred common type when `ptype = NULL`). Positions corresponding to NA indices in the underlying `vecvec` structure are filled with NA.

See Also

`vecvec()` to create a `vecvec`; `vctrs::vec_ptype_common()` for the type inference rules; `vctrs::vec_cast()` for the casting rules.

Examples

```

vv <- vecvec(1:3, c(4.5, 5.5))

# Automatic type inference: integer + double -> double
unvecvec(vv)

# Force a specific output type
unvecvec(vv, ptype = character())

```

vecvec

Create a vector of vectors

Description**[Stable]**

A `vecvec` is a vector that holds elements of different types without coercing them to a common type. Unlike a list of vectors, a `vecvec` behaves as a flat vector (hence vector of vectors). This means that you can operations (such as indexing, arithmetic, and statistics) apply across all elements of a `vecvec` as if they were combined into a single vector.

Mixed-type vectors can be useful if you need to store heterogeneous data in a vector-like structure. In most cases, I believe this is bad practice for data analytics, but this could be useful for tidying up messy data. The most valuable use case for `vecvec` is as a data structure for mixed-type semantic vectors. This package is used by `mixtime` and `distributional` to create vectors of time with different chronons and distributions with different shapes.

To convert a `vecvec` back to a plain typed vector, use `unvecvec()`, which casts all elements to a common type via `vctrs::vec_cast()`.

Usage

```
vecvec(...)
```

Arguments

... Vectors to combine. Each vector is stored as a separate typed slot; no type coercion is performed.

Value

A `vecvec` object whose length equals the total number of elements across all input vectors.

See Also

`unvecvec()` to coerce a `vecvec` to a single-typed vector; `is_vecvec()` to test whether an object is a `vecvec`.

Examples

```
# Mixed types are preserved without coercion
vv <- vecvec(Sys.Date(), rnorm(3), letters)
vv

# .[i] Indexing works like a flat vector
vv[c(1L, 3L, 7L)]

# .[[i]] drops to the original vector type
vv[[2L]]
```

vecvec_apply	<i>Apply a function to each vector of the vecvec</i>
--------------	--

Description

The `vecvec_apply()` function applies a function `.f` to each vector in the `vecvec` vectors.

Usage

```
vecvec_apply(x, .f, ...)
```

Arguments

<code>x</code>	A <code>vecvec</code> object
<code>.f</code>	A function to apply to each vector
<code>...</code>	Additional arguments passed to <code>.f</code>

Value

A `vecvec` data type with the same structure as `x` but with each vector transformed by `.f`.

vecvec_apply_fn	<i>Function factory for vecvec_apply</i>
-----------------	--

Description

The `vecvec_apply_fn()` function is a function factory that creates applies the function `.f` to each vector and optionally simplifies the result with `[unvecvec()]`. The function matches the forms of the original function `.f` and can be used to define methods for generic functions that apply to `vecvec` objects. If `.f` is a primitive function, the resulting function will have a `apply` over an argument `x` and pass through `...`

Usage

```
vecvec_apply_fn(.f, ptype = NULL, SIMPLIFY = !is.null(ptype))
```

Arguments

.f	A function to apply to each vector
ptype	A prototype to simplify to. If NULL, the result will be a vecvec object. If not NULL, the result will be simplified to the type of ptype if possible.
SIMPLIFY	If TRUE, the [unvecvec()] will be applied to the result of vecvec_apply(), using ptype as the target type. If FALSE, the result will always be a vecvec object.

Value

A function that applies .f to each vector of a vecvec object and optionally simplifies the result.

vecvec_register	<i>Register methods for a vecvec subclass</i>
-----------------	---

Description

Call `vecvec_register()` inside your package's `.onLoad()` function to register the S3 methods that allow a custom `vecvec` subclass to participate in the `vctrs` vector system.

Usage

```
vecvec_register(x)
```

Arguments

x	An S7 class object that extends <code>class_vecvec</code> . Typically the class object created by <code>S7::new_class()</code> in your package, e.g. <code>class_myvec</code> .
---	---

Details

Specifically, `vecvec_register()` registers:

- `vec_cast.<class>.*` methods, so that other types can be cast *to* your `vecvec` subclass.
- `vec_cast.*.<class>` methods, so that your `vecvec` subclass can be cast *from* other types.

Value

NULL, invisibly. Called for its side effects.

Examples

```
## Not run:
# In your package, define a vecvec subclass:
class_myvec <- S7::new_class(
  "myvec",
  parent = vecvec::class_vecvec
)

# Then register it in .onLoad():
.onLoad <- function(libname, pkgname) {
  S7::methods_register()
  vecvec::vecvec_register(class_myvec)
}

## End(Not run)
```

Index

`class_vecvec`, 2, 7
`cor (masked-cor)`, 3
`cov (masked-cor)`, 3

`is_vecvec`, 3
`is_vecvec()`, 5

`masked-cor`, 3

`S7::new_class()`, 7
`stats::cor`, 3, 4
`stats::cor()`, 4
`stats::cov`, 3, 4
`stats::cov()`, 4
`stats::var`, 3, 4
`stats::var()`, 4

`unvecvec`, 4
`unvecvec()`, 5

`var (masked-cor)`, 3
`vctrs::vec_cast()`, 4, 5
`vctrs::vec_is`, 2
`vctrs::vec_ptype_common()`, 4
`vecvec`, 5, 7
`vecvec()`, 2–4
`vecvec_apply`, 6
`vecvec_apply_fn`, 6
`vecvec_register`, 7